

HEXI 10.2K



- ◆ Wall-mounted or ground installation.
- ◆ Support OEM/ODM.
- ◆ Intelligent BMS management, WIFI module optional.
- ◆ Built-in display for easy monitor.
- ◆ All-in-one home style,easy to install.
- ◆ Excellent service life,5 years warranty.

HEXI-10.2K

Main Parameter	
Battery Chemistry	LiFeP04
Nominal Capacity(Ah)	200
Nominal Voltage (V)	51.2V
Operating Voltage(V)	46.4~57.6
Nominal Energy(kWh)	10.24
Usable Energy(kWh)	9.22 (90%DOD)
Scalability	Max.15 pcs pack in parallel
Rated DC Power(kW)	4.1
Max DC Power(kW)	6.14
Charge/Discharge Current (A)	Recommend:80 Max:120
Other Parameter	
Recommend Depth of Discharge	≤85%rh
Dimension(W/D/H, mm)	≤85%rh
Weight Approximate(kg)	≤2000m
IP Rating of Enclosure	15pcs
Operating Temperature	IP54
Storage Temperature	95.0Kg
Humidity	519*204*712(mm)
Altitude	UN38.3, CE-MEC, ROHS, IEC62619
Cycle Life	≥6000 times
Installation	CAN, RS485, RS232
Cooling Mode	-20℃~60℃
Communication Port	0℃~60℃
Warranty Period	5+5 years
Certification	UN38.3, CE, ROHS, IEC62619
The current is affected by temperature and SOC	

